Processor settings
CHR no sub

Categories		2-way Loudspeaker									
Model Name		CHR15		CHR12		CHR10		CHR15M		CHR12M	
library name		CHR15	CHR15_foh	CHR12	CHR12_foh	CHR10	CHR10_foh	CHR15M	CHR15M_moni	CHR12M	CHR12M_moni
Drive Mode		Passive	Passive	Passive	Passive	Passive	Passive	Passive	Passive	Passive	Passive
Output Name		Full-range	Full-range	Full-range	Full-range	Full-range	Full-range	Full-range	Full-range	Full-range	Full-range
Gain	(dB)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Delay	(ms)	none	none	none	none	none	none	none	none	none	none
Polality		Normal	Normal	Normal	Normal	Normal	Normal	Normal	Normal	Normal	Normal
HPF	Freq (Hz)	37.5	36.5	40.0	37.5	45.0	45.0	40.0	45.0	45.0	54.6
	Slope (dB)	24	24	24	24	24	24	24	24	24	24
	Type	Butterworth	Butterworth	Butterworth	Butterworth	Butterworth	Butterworth	Butterworth	Butterworth	Butterworth	Butterworth
LPF	Freq (Hz)			-	-			-	-		
	Slope (dB)			-	-			-	-		
	Type			-	-			-	-		
PEQ1	Freq (Hz)	60.0	61.3	63.0	63.0	71.0	71.0	67.0	67.0	71.0	130.0
	Level (dB)	8.5	13.5	5.5	9.0	7.0	9.0	7.5	6.0	5.0	-6.0
	Type	Bell	Bell	Bell	Bell	Bell	Bell	Bell	Bell	Bell	Bell
	Q	3.8	5.0	2.4	2.4	2.5	2.5	2.4	3.2	2.4	2.8
	Bandwidth	0.379	0.288	0.597	0.597	0.573	0.573	0.597	0.449	0.597	0.513
PEQ2	Freq (Hz)	212	212	230	230	250	250	118	160	125	500
	Level (dB)	4.0	4.0	1.8	1.8	-1.5	-1.5	-2.0	-2.0	-3.0	-1.5
	Type	Bell	Bell	Bell	Bell	Bell	Bell	Bell	Bell	Bell	Bell
	Q	5.0	5.0	1.5	1.5	2.0	2.0	3.0	1.5	3.3	2.5
	Bandwidth	0.288	0.288	0.945	0.945	0.714	0.714	0.479	0.945	0.436	0.573
PEQ3	Freq (Hz)	410	410	670	670	1450	1450	1600	1600	500	850
	Level (dB)	2.0	2.0	-2.0	-2.0	-3.0	-3.0	1.2	1.2	-2.0	-3.0
	Type	Bell	Bell	Bell	Bell	Bell	Bell	Bell	Bell	Bell	Bell
	Q	5.0	5.0	3.5	3.5	4.2	4.2	1.5	1.5	2.0	5.0
	Bandwidth	0.288	0.288	0.411	0.411	0.343	0.343	0.945	0.945	0.714	0.288
PEQ4	Freq (Hz)	1,320	1,320	972	972	2,800	2,800	3000	3000	2,300	2,300
	Level (dB)	-1.0	-1.0	-2.0	-2.0	-2.0	-2.0	-1.5	-1.5	-2.0	-2.0
	Type	Bell	Bell	Bell	Bell	Bell	Bell	Bell	Bell	Bell	Bell
	Q	2.2	2.2	2.5	2.5	4.2	4.2	3.0	3.0	4.7	4.7
	Bandwidth	0.650	0.650	0.573	0.573	0.343	0.343	0.479	0.479	0.306	0.306
PEQ5	Freq (Hz)	4,750	4,750	2,050	2,050	4,500	4,500	4,500	7,500	3,750	3,550
	Level (dB)	-1.5	-2.0	1.5	1.5	-1.5	-1.5	2.0	3.0	-3.0	-3.0
	Type	Bell	Bell	Bell	Bell	Bell	Bell	Bell	Bell	Bell	Bell
	Q	1.3	1.3	1.5	1.5	4.5	4.5	4.0	1.0	4.7	4.2
	Bandwidth	1.084	1.084	0.945	0.945	0.320	0.320	0.360	1.388	0.306	0.343
PEQ6	Freq (Hz)	12,500	12,500	10,000	10,000	14,000	14,000	7,500	18,000	15,000	15,000
	Level (dB)	3.0	3.0	-1.0	-1.0	-3.0	-3.0	3.0	-3.5	-7.0	-6.50
	Type	Bell	Bell	Bell	Bell	Bell	Bell	Bell	Bell	Bell	Bell
	Q	1.8	1.8	1.2	1.2	2.7	2.7	1.0	2.0	2.0	2.0
	Bandwidth	0.792	0.792	1.170	1.170	0.531	0.531	1.388	0.714	0.714	0.714
Limiter	Threshold	500W	500W	500W	500W	350W	350W	550W	550W	500W	500W
	Attack	MID	MID	MID	MID	MID	MID	MID	MID	MID	MID
	Release	MID	MID	MID	MID	MID	MID	MID	MID	MID	MID